

producto	largo	ancho	alto	altura total	peso	tensión (V)	capacidad nominal (Ah)	Capacidad Nominal (Ah) hasta alcanzar voltaje final por celda				marca	terminal
								10 HR - 1.80V/cell	8HR - 1.750V/cell	5HR - 1.75V/cell	1HR - 1.60V/cell		
BSLA-21000-CPB	170	72	205	212	6	2	100	105	100	95	67	Probattery	T7
BSLA-21500-CPB	170	98	205	212	8.5	2	150	156	150	140	100	Probattery	T11
BSLA-22000-CPB	170	110	328	350	12.7	2	200	210	200	180	134	Probattery	T11
BSLA-22500-CPB	170	110	328	350	14.5	2	250	260	250	225	168	Probattery	T11
BSLA-23000-CPB	170	150	328	350	17.5	2	300	312	300	270	201	Probattery	T11
BSLA-23500-CPB	170	150	328	350	19	2	350	365	350	329	230	Probattery	T11
BSLA-24000-CPB	210	175	330	350	26	2	400	417	400	360	260	Probattery	T11
BSLA-24500-CPB	210	175	330	350	27.3	2	450	469	450	400	290	Probattery	T11
BSLA-25000-CPB	240	170	330	350	28.5	2	500	525	500	450	330	Probattery	T11
BSLA-26000-CPB	300	175	330	350	35	2	600	630	600	540	400	Probattery	T11
BSLA-27000-CPB	300	175	330	350	38.4	2	700	730	700	640	460	Probattery	T11
BSLA-28000-CPB	410	175	330	351	50	2	800	830	800	720	520	Probattery	T11
BSLA-29000-CPB	410	175	330	351	52.5	2	900	940	900	800	580	Probattery	T11
BSLA-210000-CPB	475	175	328	350	57	2	1000	1042	1000	900	660	Probattery	T11
BSLA-212000-CPB	475	175	328	350	63	2	1200	1250	1200	1080	820	Probattery	T11
BSLA-215000-CPB	400	350	343	375	94	2	1500	1560	1500	1350	1000	Probattery	T11
BSLA-218000-CPB	400	350	343	375	100.8	2	1800	1875	1800	1600	1160	Probattery	T11
BSLA-220000-CPB	490	350	343	375	115	2	2000	2080	2000	1800	1320	Probattery	T11
BSLA-225000-CPB	490	350	343	375	132.2	2	2500	2600	2500	2250	1680	Probattery	T11
BSLA-230000-CPB	712	350	343	375	171	2	3000	3120	3000	2700	2010	Probattery	T11
BSLA-235000-CPB	712	350	343	375	188.2	2	3500	3640	3500	3185	2300	Probattery	T11